



## EdictFRD

**FINISH (ACCENTS):** Satin Carbon TeXtreme (Shadow, Red)

<b>WEIGHT</b>	10.0kg, 22.0lb
<b>FRAME</b>	Felt FRD XC, UHC Ultimate + TeXtreme carbon fiber, DMC w/ InsideOut construction, full carbon dropouts, 100mm FAST suspension, ControlTaper head tube, post disc mount, replaceable derailleur hanger, standard 73mm threaded bottom bracket, 12 x 142mm w/ Syntace style thru axle, internal derailleur cable routing, Ø30.9mm seatpost size, Shimano E-type low direct FD mount
<b>SHOCK</b>	RockShox Monarch XX w/ custom tune, XLoc Full Sprint remote lockout, 165 x 38mm
<b>FORK</b>	RockShox RS1, 120mm travel, carbon, inverted, predictive steering, post style disc mount, XLoc Full Sprint single action front & rear remote lockout
<b>HEADSET</b>	FSA No.42 integrated tapered Aheadset, carbon custom cone spacer 1 x 8mm + 3 x 5mm straight carbon spacers, w/ Felt Tornado aluminum top cap
<b>STEM</b>	Easton EC90 SL carbon threadless 1-1/8" +/- 10° rise for Ø31.8mm handlebar w/ titanium hardware: SM - 80mm MD - 80mm LG - 90mm XL - 100mm
<b>HANDLEBAR</b>	Easton EC70 Taper Wall carbon, flat Ø31.8mm 9° sweep, 720mm width
<b>GRIPS</b>	ESI Racers Edge, silicon
<b>BAR ENDS/CAPS</b>	ESI end plugs
<b>SHIFTERS</b>	SRAM XX1 Grip Shift 1 x 11-speed
<b>REAR DERAILLEUR</b>	SRAM XX1 Type 2 long cage

<b>CRANKSET</b>	RaceFace carbon Next single: SM - 170mm MD/LG/XL - 175mm
<b>CHAINWHEEL</b>	RaceFace NW 32T
<b>BOTTOM BRACKET</b>	SRAM XX GXP sealed threaded
<b>CHAIN</b>	SRAM
<b>FREEWHEEL / CASSETTE</b>	SRAM XX1 11-speed 10-42T
<b>BRAKE LEVERS</b>	SRAM XX carbon
<b>FRONT BRAKE</b>	SRAM XX disc w/ HSX 180mm rotor
<b>REAR BRAKE</b>	SRAM XX disc w/ HSX 160mm rotor
<b>CABLES</b>	Felt All-Weather Sealed Slick
<b>SADDLE</b>	WTB SL8 Carbon rails
<b>SEAT POST</b>	Easton EC70 Taper Wall monocoque carbon: SM - Ø30.9 x 350mm MD/LG/XL - Ø30.9 x 400mm
<b>SEAT POST CLAMP</b>	Aluminum 7075 CNC w/ titanium bolt Ø31.8mm
<b>RIMS / WHEELSET</b>	SRAM Carbon Rise 60 29"
<b>FRONT HUB</b>	SRAM Predictive Steering hub for RS1 forks.
<b>REAR HUB</b>	SRAM XD driver
<b>SPOKES</b>	SRAM Carbon Rise
<b>TIRES</b>	Schwalbe Nobby Nic EVO TL Easy, folding 29" x 2.1"

### GEOMETRY CHART:

SIZE:	SM (16")	MD (18")	LG (20")	XL (22")
<b>HA</b>				
<b>SA</b>				
<b>TT HORIZ</b>				
<b>HT LENGTH</b>				
<b>SEAT TUBE C-T</b>				
<b>BB DROP</b>				
<b>CS</b>				
<b>WHEELBASE</b>				
<b>STANDOVER</b>				
<b>RAKE</b>				
<b>REACH</b>				
<b>STACK</b>				



## Edict1

**FINISH (ACCENTS):** Satin Carbon (Blue, Charcoal)

<b>WEIGHT</b>	10.6kg, 23.3lb
<b>FRAME</b>	Felt XC, UHC Performance + TeXtreme carbon fiber, DMC w/ InsideOut construction, full carbon dropouts, 100mm FAST suspension, ControlTaper head tube, post disc mount, replaceable derailleur hanger, standard 73mm threaded bottom bracket, 12 x 142mm w/ Syntace style thru axle, internal derailleur cable routing, Ø30.9mm seat-post size, Shimano E-type low direct FD mount
<b>SHOCK</b>	RockShox Monarch RT3 w/ custom tune, 165 x 38mm
<b>FORK</b>	RockShox Sid RL, 100mm travel, PushLoc remote lockout, adjustable rebound, tapered aluminum steerer, magnesium lowers, 15mm Maxle, post style disc mount
<b>HEADSET</b>	FSA No.42 integrated tapered Aheadset, custom cone spacer 1 x 8mm + 3 x 5mm straight spacers, w/ Felt Tornado aluminum top cap
<b>STEM</b>	Felt MTB 3D-forged threadless 1-1/8" +/- 7° rise for Ø31.8mm handlebar w/ black Cr-Mo bolts: SM - 80mm MD - 80mm LG - 90mm XL - 100mm
<b>HANDLEBAR</b>	Felt MTB carbon, flat Ø31.8mm 9° sweep, 720mm width
<b>GRIPS</b>	ESI Racers Edge, silicon
<b>BAR ENDS/CAPS</b>	ESI end plugs
<b>SHIFTERS</b>	SRAM X1 11-speed
<b>REAR DERAILLEUR</b>	SRAM X01
<b>CRANKSET</b>	SRAM X01 carbon, single: SM - 170mm MD/LG/XL - 175mm

<b>CHAINWHEEL</b>	SRAM 30T
<b>BOTTOM BRACKET</b>	GXP sealed threaded
<b>CHAIN</b>	SRAM
<b>FREEWHEEL / CASSETTE</b>	SRAM 11-speed 10-42T
<b>BRAKE LEVERS</b>	SRAM X0
<b>FRONT BRAKE</b>	SRAM X0 disc w/180mm rotor
<b>REAR BRAKE</b>	SRAM X0 disc w/160mm rotor
<b>CABLES</b>	Felt All-Weather Sealed Slick
<b>SADDLE</b>	WTB Silverado w/ Cr-Mo rails
<b>SEAT POST</b>	Felt UHC Performance carbon shaft, 2-bolt micro-adjust, low-profile forged head & forged rail clamps: SM - Ø30.9 x 350mm MD/LG/XL - Ø30.9 x 400mm
<b>SEAT POST CLAMP</b>	Aluminum 6061 CNC cold-forged w/ barrel nut design, Ø34.9mm
<b>RIMS / WHEEL-SET</b>	Easton EA70 XCT 29"
<b>FRONT HUB</b>	Easton EA70 XCT 15mm axle
<b>REAR HUB</b>	Easton EA70 XCT 142 x 12mm axle
<b>SPOKES</b>	Easton EA70 XCT
<b>TIRES</b>	Schwalbe Racing Ralph Evo, TL Ready folding 29" x 2.1"

### GEOMETRY CHART:

SIZE:	SM (16")	MD (18")	LG (20")	XL (22")
<b>HA</b>	71.5	71.5	71.5	71.5
<b>SA</b>	73	73	73	73
<b>TT HORIZ</b>	578	603	628	650
<b>HT LENGTH</b>	100	110	120	140
<b>SEAT TUBE C-T</b>	15.5	18	20	22.5
<b>BB DROP</b>	42	42	42	42
<b>CS</b>	450	450	450	450
<b>WHEELBASE</b>	1078	1103	1128	1150
<b>STANDOVER</b>	700	705	725	763
<b>RAKE</b>	46	46	46	46
<b>REACH</b>	393	415	436	452
<b>STACK</b>	602	612	621	640



## Edict2

**FINISH (ACCENTS):** Satin Carbon (Green, Blue)

<b>WEIGHT</b>	11.6kg, 25.5lb
<b>FRAME</b>	Felt XC, UHC Performance carbon fiber, DMC w/ InsideOut construction, full carbon dropouts, 100mm FAST suspension, ControlTaper head tube, post disc mount, replaceable derailleur hanger, standard 73mm threaded bottom bracket, 12 x 142mm w/ Syntace style thru axle, internal derailleur cable routing, Ø30.9mm seatpost size, Shimano E-type low direct FD mount
<b>SHOCK</b>	RockShox Monarch RT3 w/ custom tune, 165 x 38mm
<b>FORK</b>	RockShox Reba RL, 100mm travel, Solo Air, PushLoc remote lockout, adjustable rebound, tapered aluminum steerer, magnesium lowers, 15mm Maxle, post style disc mount
<b>HEADSET</b>	FSA No.42 integrated tapered Aheadset, custom cone spacer 1 x 8mm + 3 x 5mm straight spacers, w/ Felt Tornado aluminum top cap
<b>STEM</b>	Felt MTB 3D-forged threadless 1-1/8" +/- 7° rise for Ø31.8mm handlebar w/ black Cr-Mo bolts: SM - 80mm MD - 80mm LG - 90mm XL - 100mm
<b>HANDLEBAR</b>	Felt MTB carbon, flat Ø31.8mm 9° sweep, 720mm width
<b>GRIPS</b>	ESI Racers Edge, silicon
<b>BAR ENDS/CAPS</b>	ESI end plugs
<b>SHIFTERS</b>	Shimano SLX Rapid-Fire 2 x 10-speed
<b>FRONT DERAILLEUR</b>	Shimano SLX dual pull, low direct mount
<b>REAR DERAILLEUR</b>	Shimano XT Shadow Plus long cage

<b>CRANKSET</b>	Shimano XT Hollowtech II double: SM - 170mm MD/LG/XL - 175mm
<b>CHAINWHEEL</b>	Shimano 38/24T
<b>BOTTOM BRACKET</b>	Shimano sealed threaded
<b>CHAIN</b>	Shimano
<b>FREEWHEEL / CASSETTE</b>	Shimano 10-speed 11-36T
<b>BRAKE LEVERS</b>	Shimano Deore disc
<b>FRONT BRAKE</b>	Shimano Deore disc w/180mm 6-bolt rotor
<b>REAR BRAKE</b>	Shimano Deore disc w/160mm 6-bolt rotor
<b>CABLES</b>	Felt All-Weather Sealed Slick
<b>SADDLE</b>	WTB Silverado Cr-Mo rails
<b>SEAT POST</b>	Felt butted 6061 aluminum w/ 2-bolt micro-adjust 15mm offset: SM - Ø30.9 x 350mm MD/LG/XL - Ø30.9 x 400mm
<b>SEAT POST CLAMP</b>	Aluminum 6061 CNC cold-forged w/ barrel nut design, Ø34.9mm
<b>RIMS / WHEEL-SET</b>	Easton XR 29"
<b>FRONT HUB</b>	Easton XR 15mm axle
<b>REAR HUB</b>	Easton XR 142 x 12mm axle
<b>SPOKES</b>	Easton XR
<b>TIRES</b>	Schwalbe Racing Ralph Performance folding 29" x 2.25"

### GEOMETRY CHART:

SIZE:	SM (16")	MD (18")	LG (20")	XL (22")
<b>HA</b>	71.5	71.5	71.5	71.5
<b>SA</b>	73	73	73	73
<b>TT HORIZ</b>	578	603	628	650
<b>HT LENGTH</b>	100	110	120	140
<b>SEAT TUBE C-T</b>	15.5	18	20	22.5
<b>BB DROP</b>	42	42	42	42
<b>CS</b>	450	450	450	450
<b>WHEELBASE</b>	1078	1103	1128	1150
<b>STANDOVER</b>	700	705	725	763
<b>RAKE</b>	46	46	46	46
<b>REACH</b>	393	415	436	452
<b>STACK</b>	602	612	621	640



## Edict3

**FINISH (ACCENTS):** Satin Charcoal (Fluoro Red)

<b>WEIGHT</b>	12.4kg, 27.2lb
<b>FRAME</b>	Felt XC, UHC Performance carbon fiber, DMC w/ InsideOut construction, full carbon dropouts, 100mm FAST suspension, ControlTaper head tube, post disc mount, replaceable derailleur hanger, standard 73mm threaded bottom bracket, 12 x 142mm w/ Syntace style thru axle, internal derailleur cable routing, Ø30.9mm seatpost size, Shimano E-type low direct FD mount
<b>SHOCK</b>	RockShox Monarch RT w/ custom tune, 165 x 38mm
<b>FORK</b>	RockShox Reba RL, 100mm travel, Solo Air, PushLoc remote lockout, adjustable rebound, tapered aluminum steerer, magnesium lowers, 15mm Maxle, post style disc mount
<b>HEADSET</b>	FSA No.42 integrated tapered Aheadset, custom cone spacer 1 x 8mm + 3 x 5mm straight spacers, w/ Felt Tornado aluminum top cap
<b>STEM</b>	Felt MTB 3D-forged threadless 1-1/8" +/- 7° rise for Ø31.8mm handlebar w/ black Cr-Mo bolts: SM - 80mm MD - 80mm LG - 90mm XL - 100mm
<b>HANDLEBAR</b>	Felt MTB double-buttet 6061 aluminum, Ø31.8mm 5mm rise x 9° sweep, 720mm width
<b>GRIPS</b>	Felt Wing Grip, Lock-On
<b>BAR ENDS/CAPS</b>	Felt Bubble-Tech F-Wing
<b>SHIFTERS</b>	Shimano Deore Rapid-Fire 2 x 10-speed
<b>FRONT DERAILEUR</b>	Shimano Deore dual pull, low direct mount
<b>REAR DERAILEUR</b>	Shimano XT Shadow Plus long cage

<b>CRANKSET</b>	Shimano Deore double: SM - 170mm MD/LG/XL - 175mm
<b>CHAINWHEEL</b>	Shimano 38/24T
<b>BOTTOM BRACKET</b>	Shimano sealed threaded
<b>CHAIN</b>	Shimano
<b>FREEWHEEL / CASSETTE</b>	Shimano 10-speed 11-36T
<b>BRAKE LEVERS</b>	Shimano Deore
<b>FRONT BRAKE</b>	Shimano Deore disc w/180mm 6-bolt rotor
<b>REAR BRAKE</b>	Shimano Deore disc w/160mm 6-bolt rotor
<b>CABLES</b>	Felt All-Weather Sealed Slick
<b>SADDLE</b>	WTB Silverado Cr-Mo rails
<b>SEAT POST</b>	Felt butted 6061 aluminum w/ 2-bolt micro-adjust 15mm offset: SM - Ø30.9 x 350mm MD/LG/XL - Ø30.9 x 400mm
<b>SEAT POST CLAMP</b>	Aluminum 6061 CNC cold-forged w/ barrel nut design, Ø34.9mm
<b>RIMS / WHEEL-SET</b>	WTB Speed Disc i23, 29" double-wall aluminum w/ eyelets
<b>FRONT HUB</b>	Forged aluminum, 6 bolt disc mount 32H, 15mm axle
<b>REAR HUB</b>	Forged aluminum, 6-bolt disc mount, 32H, 142 x 12mm axle
<b>SPOKES</b>	2.0/1.8mm double-buttet stainless steel w/ aluminum nipples
<b>TIRES</b>	Schwalbe Racing Ralph Performance folding 29" x 2.25"

### GEOMETRY CHART:

SIZE:	SM (16")	MD (18")	LG (20")	XL (22")
<b>HA</b>	71.5	71.5	71.5	71.5
<b>SA</b>	73	73	73	73
<b>TT HORIZ</b>	578	603	628	650
<b>HT LENGTH</b>	100	110	120	140
<b>SEAT TUBE C-T</b>	15.5	18	20	22.5
<b>BB DROP</b>	42	42	42	42
<b>CS</b>	450	450	450	450
<b>WHEELBASE</b>	1078	1103	1128	1150
<b>STANDOVER</b>	700	705	725	763
<b>RAKE</b>	46	46	46	46
<b>REACH</b>	393	415	436	452
<b>STACK</b>	602	612	621	640



## Edict5

**FINISH (ACCENTS):** Satin Carbon (Fluoro Red, Grey)

<b>WEIGHT</b>	13kg, 28.6lb
<b>FRAME</b>	Felt XC, UHC Performance carbon fiber, DMC w/ InsideOut construction, full carbon dropouts, 100mm FAST suspension, ControlTaper head tube, post disc mount, replaceable derailleur hanger, standard 73mm threaded bottom bracket, 12 x 142mm w/ Syntace style thru axle, internal derailleur cable routing, Ø30.9mm seatpost size, Shimano E-type low direct FD mount
<b>SHOCK</b>	RockShox Monarch R w/ custom tune, 165 x 38mm
<b>FORK</b>	Suntour Raidon XC-LOR, 100mm travel, crown lock out, adjustable rebound, tapered aluminum steerer tube, forged aluminum crown, magnesium lowers, 15mm QR, post style disc mount
<b>HEADSET</b>	FSA No.42 integrated tapered Aheadset, custom cone spacer 1 x 8mm + 3 x 5mm straight spacers, w/ Felt Tornado aluminum top cap
<b>STEM</b>	Felt MTB 3D-forged threadless 1-1/8" +/- 7° rise for Ø31.8mm handlebar w/ black Cr-Mo bolts: SM - 80mm MD - 80mm LG - 90mm XL - 100mm
<b>HANDLEBAR</b>	Felt MTB double-buttetted 6061 aluminum, Ø31.8mm 5mm rise x 9° sweep, 720mm width
<b>GRIPS</b>	Felt Wing Grip, double-density
<b>BAR ENDS/CAPS</b>	Felt Bubble-Tech F-Wing
<b>SHIFTERS</b>	Shimano Deore Rapid-Fire 2 x 10-speed
<b>FRONT DERAILEUR</b>	Shimano Deore low direct mount bottom pull
<b>REAR DERAILEUR</b>	Shimano Deore Shadow, long cage

<b>CRANKSET</b>	Shimano Deore double: SM - 170mm MD/LG/XL - 175mm
<b>CHAINWHEEL</b>	Shimano 38/24T
<b>CHAINGUIDE</b>	
<b>BOTTOM BRACKET</b>	Shimano sealed threaded
<b>CHAIN</b>	Shimano
<b>FREEWHEEL / CASSETTE</b>	Shimano 10-speed 11-36T
<b>BRAKE LEVERS</b>	Shimano M355 hydraulic disc brake
<b>FRONT BRAKE</b>	Shimano M355 hydraulic disc brake w/ Center Lock 180mm rotor
<b>REAR BRAKE</b>	Shimano M355 hydraulic disc brake w/ Center Lock 160mm rotor
<b>CABLES</b>	Felt All-Weather Sealed Slick
<b>SADDLE</b>	WTB Silverado
<b>SEAT POST</b>	Felt butted 6061 aluminum micro-adjust 15mm offset: SM - Ø30.9 x 350mm MD/LG/XL - Ø30.9 x 400mm
<b>SEAT POST CLAMP</b>	Aluminum 6061 CNC cold-forged w/ barrel nut design, Ø34.9mm
<b>RIMS / WHEEL-SET</b>	Aluminum double-wall i23, 29"
<b>FRONT HUB</b>	Forged aluminum, Center Lock disc mount 32H, 15mm axle
<b>REAR HUB</b>	Forged aluminum, Center Lock disc mount, 32H, 142 x 12mm axle
<b>SPOKES</b>	2.0mm stainless steel w/ aluminum nipples
<b>TIRES</b>	Schwalbe Rapid Rob folding 29" x 2.25"

### GEOMETRY CHART:

SIZE:	SM (16")	MD (18")	LG (20")	XL (22")
<b>HA</b>	71.5	71.5	71.5	71.5
<b>SA</b>	73	73	73	73
<b>TT HORIZ</b>	578	603	628	650
<b>HT LENGTH</b>	100	110	120	140
<b>SEAT TUBE C-T</b>	15.5	18	20	22.5
<b>BB DROP</b>	42	42	42	42
<b>CS</b>	450	450	450	450
<b>WHEELBASE</b>	1078	1103	1128	1150
<b>STANDOVER</b>	700	705	725	763
<b>RAKE</b>	46	46	46	46
<b>REACH</b>	393	415	436	452
<b>STACK</b>	602	612	621	640



## Edict50

**FINISH (ACCENTS):** Satin Steel Blue (Orange)

<b>WEIGHT</b>	13.6kg, 29.9lb
<b>FRAME</b>	Felt XC, double-buttet 7005 aluminum, Hydroform, 100mm travel, ControlTaper head tube, post disc mount, replaceable derailleur hanger, standard 73mm threaded bottom bracket, 12 x 142mm w/ Syntace style through axle, Ø30.9mm seatpost size, Ø34.9mm high clamp front derailleur
<b>SHOCK</b>	RockShox Monarch RT w/ custom tune, 165 x 38mm
<b>FORK</b>	RockShox Recon Gold, 100mm travel, Solo Air, PushLoc remote lockout, adjustable rebound, tapered aluminum steerer, magnesium lowers, 15mm Maxle, post style disc mount
<b>HEADSET</b>	FSA No.42 integrated tapered Aheadset, custom cone spacer 1 x 8mm + 3 x 5mm straight spacers, w/ Felt Tornado aluminum top cap
<b>STEM</b>	Felt MTB 3D-forged threadless 1-1/8" +/- 7° rise for Ø31.8mm handlebar w/ black Cr-Mo bolts: SM - 80mm MD - 80mm LG - 90mm XL - 100mm
<b>HANDLEBAR</b>	Felt MTB double-buttet 6061 aluminum, Ø31.8mm, 15mm rise x 9° sweep, 720mm width
<b>GRIPS</b>	Felt Wing Grip, double-density
<b>BAR ENDS/CAPS</b>	Felt Bubble-Tech F-Wing
<b>SHIFTERS</b>	Shimano Deore Rapid-Fire 3 x 10-speed
<b>FRONT DERAILEUR</b>	Shimano Deore high clamp Ø34.9mm, bottom pull
<b>REAR DERAILEUR</b>	Shimano XT long cage
<b>CRANKSET</b>	Shimano Deore Hollowtech II triple: SM - 170mm MD/LG/XL - 175mm

<b>CHAINWHEEL</b>	Shimano 40/30/22T
<b>BOTTOM BRACKET</b>	Shimano sealed threaded
<b>CHAIN</b>	Shimano
<b>FREEWHEEL / CASSETTE</b>	Shimano 10-speed 11-36T
<b>BRAKE LEVERS</b>	Shimano M355 hydraulic disc brake
<b>FRONT BRAKE</b>	Shimano M355 hydraulic disc brake w/ 180mm rotor
<b>REAR BRAKE</b>	Shimano M355 hydraulic disc brake w/ 160mm rotor
<b>CABLES</b>	Felt All-Weather Sealed Slick
<b>SADDLE</b>	WTB Silverado
<b>SEAT POST</b>	Felt butted 6061 aluminum w/ 2-bolt micro-adjust 15mm offset: SM - Ø30.9 x 350mm MD/LG/XL - Ø30.9 x 400mm
<b>SEAT POST CLAMP</b>	Aluminum 6061 CNC cold-forged w/ barrel nut design, Ø34.9mm
<b>RIMS / WHEEL-SET</b>	WTB Speed Disc i23, 29" double-wall aluminum w/ eyelets
<b>FRONT HUB</b>	Forged aluminum, Center Lock disc mount 32H, 15mm axle
<b>REAR HUB</b>	Forged aluminum, Center Lock disc mount, 32H, 142 x 12mm axle
<b>SPOKES</b>	2.0/1.8mm double-buttet stainless steel w/ aluminum nipples
<b>TIRES</b>	Schwalbe Rapid Rob folding 29" x 2.25"

### GEOMETRY CHART:

SIZE:	SM (16")	MD (18")	LG (20")	XL (22")
<b>HA</b>	71.5	71.5	71.5	71.5
<b>SA</b>	73	73	73	73
<b>TT HORIZ</b>	578	603	628	650
<b>HT LENGTH</b>	100	110	120	140
<b>SEAT TUBE C-T</b>	15.5	18	20	22.5
<b>BB DROP</b>	42	42	42	42
<b>CS</b>	450	450	450	450
<b>WHEELBASE</b>	1078	1103	1128	1150
<b>STANDOVER</b>	700	705	725	763
<b>RAKE</b>	46	46	46	46
<b>REACH</b>	393	415	436	452
<b>STACK</b>	602	612	621	640



## Edict60

**FINISH (ACCENTS):** Gloss White (black)

<b>WEIGHT</b>	13.9kg, 30.6lb
<b>FRAME</b>	Felt XC, double-buttet 7005 aluminum, Hydroform, 100mm travel, ControlTaper head tube, post disc mount, replaceable derailleur hanger, standard 73mm threaded bottom bracket, 12 x 142mm w/ Syntace style through axle, Ø30.9mm seatpost size, Ø34.9mm high clamp front derailleur
<b>SHOCK</b>	RockShox Monarch R w/ custom tune, 165 x 38mm
<b>FORK</b>	Suntour Raidon XC-LOR, 100mm travel, crown lock out, adjustable rebound, tapered aluminum steerer tube, forged aluminum crown, magnesium lowers, 15mm QR, post style disc mount
<b>HEADSET</b>	FSA No.42 integrated tapered Aheadset, custom cone spacer 1 x 8mm + 3 x 5mm straight spacers, w/ Felt Tornado aluminum top cap
<b>STEM</b>	Felt MTB 3D-forged threadless 1-1/8" +/- 7° rise for Ø31.8mm handlebar w/ black Cr-Mo bolts: SM - 80mm MD - 80mm LG - 90mm XL - 100mm
<b>HANDLEBAR</b>	Felt MTB double-buttet 6061 aluminum, Ø31.8mm, 15mm rise x 9° sweep, 720mm width
<b>GRIPS</b>	Felt Wing Grip, double-density
<b>BAR ENDS/CAPS</b>	Felt Bubble-Tech F-Wing
<b>SHIFTERS</b>	Shimano Deore Rapid-Fire 3 x 10-speed
<b>FRONT DERAILEUR</b>	Shimano Deore high clamp Ø34.9mm, bottom pull
<b>REAR DERAILEUR</b>	Shimano Deore Shadow long cage
<b>CRANKSET</b>	Shimano Deore triple: SM - 170mm MD/LG/XL - 175mm

<b>CHAINWHEEL</b>	Shimano 44/32/22T
<b>BOTTOM BRACKET</b>	Shimano sealed threaded
<b>CHAIN</b>	Shimano
<b>FREEWHEEL / CASSETTE</b>	Shimano 10-speed 11-36T
<b>BRAKE LEVERS</b>	Shimano M355 hydraulic disc brake
<b>FRONT BRAKE</b>	Shimano M355 hydraulic disc brake w/ Center Lock 180mm rotor
<b>REAR BRAKE</b>	Forged aluminum, Center Lock disc mount, 32H, 142 x 12mm axle
<b>CABLES</b>	Felt All-Weather Sealed Slick
<b>SADDLE</b>	Felt MTB performance
<b>SEAT POST</b>	Felt butted 6061 aluminum micro-adjust 15mm offset: SM - Ø30.9 x 350mm MD/LG/XL - Ø30.9 x 400mm
<b>SEAT POST CLAMP</b>	Aluminum 6061 CNC cold-forged w/ barrel nut design, Ø34.9mm
<b>RIMS / WHEEL-SET</b>	Aluminum double-wall i23, 29"
<b>FRONT HUB</b>	Forged aluminum, Center Lock disc mount 32H, 15mm axle
<b>REAR HUB</b>	Forged aluminum, Center Lock disc mount, 32H, 142 x 12mm axle
<b>SPOKES</b>	2.0mm stainless steel w/ aluminum nipples
<b>TIRES</b>	Schwalbe Rapid Rob folding 29" x 2.25"

### GEOMETRY CHART:

SIZE:	SM (16")	MD (18")	LG (20")	XL (22")
<b>HA</b>	71.5	71.5	71.5	71.5
<b>SA</b>	73	73	73	73
<b>TT HORIZ</b>	578	603	628	650
<b>HT LENGTH</b>	100	110	120	140
<b>SEAT TUBE C-T</b>	15.5	18	20	22.5
<b>BB DROP</b>	42	42	42	42
<b>CS</b>	450	450	450	450
<b>WHEELBASE</b>	1078	1103	1128	1150
<b>STANDOVER</b>	700	705	725	763
<b>RAKE</b>	46	46	46	46
<b>REACH</b>	393	415	436	452
<b>STACK</b>	602	612	621	640