



INSTINCT 999 MSL

CRS555 / CFS555 (frame only)



TECHNOLOGY



IMPROVEMENTS

Stan's Valor Carbon Wheels: 1250g and Increased Stiffness.

Shimano XTR Trail Brakes for Reliable Performance.

High Performance Maxxis Tubeless Tires.

GEOMETRY

FRAME SIZE		SM	MD	LG	XL	XXL
HEAD ANGLE	degrees	67.7° - 69.3°	67.7° - 69.3°	67.7° - 69.3°	67.7° - 69.3°	67.7° - 69.3°
SEAT ANGLE	degrees	73.7° - 75.3°	73.7° - 75.3°	73.7° - 75.3°	73.7° - 75.3°	73.7° - 75.3°
SEAT TUBE (CENTER BB TO TOP)	(mm)	394	432	470	508	546
HORIZONTAL TOP TUBE LENGTH	(mm)	553	577	600	625	650
HEAD TUBE LENGTH	(mm)	100	110	120	130	145
CHAINSTAY LENGTH	(mm)	452	452	452	452	452
BOTTOM BRACKET DROP	(mm)	39.6 to 20.7	39.6 to 20.7	39.6 to 20.7	39.6 to 20.7	39.6 to 20.7
STANDOVER HEIGHT	(mm)	736	736	736	736	736
WHEELBASE	(mm)	1110	1134	1158	1183	1210
REACH	(mm)	378 - 395	400 - 417	420 - 437	442 - 459	464 - 480
STACK	(mm)	605 - 594	614 - 603	624 - 612	633 - 621	647 - 634

* More details on measurements on demand.

SPECIFICATIONS

FRAME	C13 Hi Mod Carbon Smoothwall Mono-coque. ABC™ Pivots. Tapered Head Tube. Press Fit BB. Internal Cable Routing. ISCG05 Tabs. RIDE-9™ Adjustable Geometry + Suspension Rate
COLOR	Matte Carbon
SIZES	S - M - L - XL - XXL
SHOCK	Fox Float CTD Remote Kashima Custom Trail Valved. SmoothLink™ Design 130mm. Rebound / Remote Climb (X-Firm ProPedal) - Trail (ProPedal) - Descend (Open) Settings / Adjustable Suspension Rate
FORK	Fox 32 Float 29 130 FIT CTD Adjust Kashima. 130mm. Rebound / Climb (Lockout) - Trail (3 Position Compression) - Descend (Open) Settings / 15mm Axle / Tapered Steerer
HEADSET	Cane Creek Forty Series: IS42mm Top / IS52mm Bottom Tapered
BRAKE LEVERS	Shimano XTR Trail
BRAKES	Shimano XTR Ice-Tec Hydraulic Disc 180mm
CASSETTE	Sram XG-1199 10-42T 11spd
CHAIN	Sram PC-XX1 11spd
CRANKS	Race Face Next SL 170-175mm 30T 11spd
BOTTOM BRACKET	Race Face Cinch 30mm BB92 Pressfit
SHIFTERS	Sram XX1 Trigger 1x11spd
F. DERAILLEUR	N/A
R. DERAILLEUR	Sram XX1 Type 2 All Mountain 11spd
F. HUB	Stan's 3.30Ti Hub / 24H / 15mm Axle
R. HUB	Stan's 3.30Ti Hub / 28H / Alloy XD Freehub / 12 x 142mm Axle
SPOKES	Sapim Laser
RIMS	Stan's Valor Carbon Tubeless Ready
TIRES	Maxxis EXO Maxx Speed Tubeless Ready F: Ardent 29" x 2.4" R: Ikon 29" x 2.35"
HANDELBAR	Race Face Next Carbon 1/2 Rise Ø35mm x 760mm x 9° Sweep
STEM	Race Face Turbine CNC 35mm 6° x 60-80mm
GRIPS	Rocky Mountain Lock On XC
SADDLE	WTB Silverado Carbon
SEATPOST	RockShox Verber Stealth 30.9mm x 355-420mm

*Price, specification and availability subject to change without notice.



INSTINCT 990 MSL

CRS554

BC EDITION



TECHNOLOGY



GEOMETRY

FRAME SIZE		SM	MD	LG	XL	XXL
HEAD ANGLE	degrees	66.7° - 68.3°	66.7° - 68.3°	66.7° - 68.3°	66.7° - 68.3°	66.7° - 68.3°
SEAT ANGLE	degrees	72.8° - 74.3°	72.8° - 74.3°	72.8° - 74.3°	72.8° - 74.3°	72.8° - 74.3°
SEAT TUBE (CENTER BB TO TOP)	(mm)	394	432	470	508	546
HORIZONTAL TOP TUBE LENGTH	(mm)	553	577	600	625	650
HEAD TUBE LENGTH	(mm)	100	110	120	130	145
CHAINSTAY LENGTH	(mm)	452	452	452	452	452
BOTTOM BRACKET DROP	(mm)	31.9 to 12.4	31.9 to 12.4	31.9 to 12.4	31.9 to 12.4	31.9 to 12.4
STANDOVER HEIGHT	(mm)	745	745	745	745	745
WHEELBASE	(mm)	1119	1143	1167	1192	1219
REACH	(mm)	367 - 384	389 - 406	409 - 426	432 - 449	453 - 470
STACK	(mm)	611 - 600	621 - 610	631 - 620	641 - 629	655 - 643

* More details on measurements on demand.

SPECIFICATIONS

FRAME	C13 Hi Mod Carbon Smoothwall Mono-coque. ABC™ Pivots. Tapered Head Tube. Press Fit BB. Internal Cable Routing. ISCG05 Tabs. RIDE-9™ Adjustable Geometry + Suspension Rate
COLOR	Matte Orange
SIZES	S - M - L - XL - XXL
SHOCK	RockShox Monarch RT3 Custom BC Valved. SmoothLink™ Design 130mm. Rebound / 3 Position Compression / Adjustable Suspension Rate
FORK	RockShox Pike RCT3 29. 140mm. Charger Damper / Rebound / Adjustable 3 Position Compression / 15mm Axle / Tapered Steerer
HEADSET	Cane Creek Forty Series: IS42mm Top / IS52mm Bottom Tapered
BRAKE LEVERS	Shimano XT
BRAKES	Shimano XT Ice-Tec Hydraulic Disc 180mm
CASSETTE	Sram XG-1195 10-42T 11spd
CHAIN	Sram PC-XX1 11spd
CRANKS	Race Face Turbine Cinch 170-175mm 30T Direct Mount 1x11spd
BOTTOM BRACKET	Race Face Cinch 30mm BB92 Pressfit
SHIFTERS	Sram X01 Trigger 1x11spd
F. DERAILLEUR	N/A
R. DERAILLEUR	Sram X01 Type 2 All Mountain 11spd
F. HUB	Stan's 3.30 Disc / 15mm Axle
R. HUB	Stan's 3.30 Disc / 6 Pawl XD Freehub / 142 x 12mm Axle
SPOKES	DT Swiss Competition
RIMS	Stan's ZTR Flow EX Tubeless Ready
TIRES	Maxxis Minion DHR II Maxx Terra EX0 Tubeless Ready 29" x 2.3"
HANDELBAR	Race Face Next 1/2 Rise Ø35mm x 760mm x 9° Sweep
STEM	Race Face Turbine 35mm 6° x 50-70mm
GRIPS	Rocky Mountain Lock On XC
SADDLE	WTB Silverado SLT Titanium
SEATPOST	RockShox Reverb Stealth 30.9mm x 355-420mm

*Price, specification and availability subject to change without notice.



INSTINCT 970 MSL

CRS552



TECHNOLOGY



IMPROVEMENTS

Race Face Turbine Cinch 30mm Crank: Lighter and Stiffer.

Stan's ZTR Flow Rims: Wider Profile for Stiffer Wheel and Bigger Tire Contact Patch.

High Performance Maxxis Folding Tires.

GEOMETRY

FRAME SIZE		XS	SM	MD	LG	XXL
HEAD ANGLE	degrees	67.7° - 69.3°	67.7° - 69.3°	67.7° - 69.3°	67.7° - 69.3°	67.7° - 69.3°
SEAT ANGLE	degrees	73.7° - 75.3°	73.7° - 75.3°	73.7° - 75.3°	73.7° - 75.3°	73.7° - 75.3°
SEAT TUBE (CENTER BB TO TOP)	(mm)	394	432	470	508	546
HORIZONTAL TOP TUBE LENGTH	(mm)	553	577	600	625	650
HEAD TUBE LENGTH	(mm)	100	110	120	130	145
CHAINSTAY LENGTH	(mm)	452	452	452	452	452
BOTTOM BRACKET DROP	(mm)	39.6 to 20.7	39.6 to 20.7	39.6 to 20.7	39.6 to 20.7	39.6 to 20.7
STANDOVER HEIGHT	(mm)	736	736	736	736	736
WHEELBASE	(mm)	1110	1134	1158	1183	1210
REACH	(mm)	378 - 395	400 - 417	420 - 437	442 - 459	464 - 480
STACK	(mm)	605 - 594	614 - 603	624 - 612	633 - 621	647 - 634

* More details on measurements on demand.

SPECIFICATIONS

FRAME	C13 Hi Mod Carbon Smoothwall Mono-coque. ABC™ Pivots. Tapered Head Tube. Press Fit BB. Internal Cable Routing. ISCG05 Tabs. RIDE-9™ Adjustable Geometry + Suspension Rate
COLOR	Matte Carbon
SIZES	S - M - L - XL - XXL
SHOCK	Fox Float CTD Remote Custom Trail Valved. SmoothLink™ Design 130mm. Rebound / Remote Climb (X-Firm ProPedal) - Trail (ProPedal) - Descend (Open) Settings / Adjustable Suspension Rate
FORK	Fox 32 Float 29 130 FIT CTD. 130mm. FIT Damper / Rebound / Climb (Lockout) - Trail (Compression) - Descend (Open) Settings / 15mm Axle / Tapered Steerer
HEADSET	Cane Creek Forty Series: IS42mm Top / IS52mm Bottom Tapered
BRAKE LEVERS	Shimano XT I-Spec Shifter Mount
BRAKES	Shimano XT Hydraulic Disc 180mm
CASSETTE	Shimano HG81 11-36T 10spd
CHAIN	Shimano HG95 10spd
CRANKS	Race Face Turbine Cinch 170-175mm Bash/36/22T 2x10spd
BOTTOM BRACKET	Race Face Cinch 30mm BB92 Pressfit
SHIFTERS	Shimano XT Rapid Fire I-Spec 2x10spd
F. DERAILLEUR	Sram XO S3 Direct Mount 2x10spd
R. DERAILLEUR	Shimano XT Shadow Plus Direct Mount 10spd
F. HUB	Shimano XT / Centerlock / 32H / 15mm Axle
R. HUB	Shimano XT / Centerlock / 32H / 12 x 142mm Axle
SPOKES	DT Swiss Competition
RIMS	Stan's ZTR Flow Tubeless Ready
TIRES	Maxxis F: Ardent EXO Folding 29" x 2.4" R: Ikon EXO Folding 29" x 2.35"
HANDELBAR	Race Face Turbine 1/2 Rise Ø35mm x 760mm x 9° Sweep
STEM	Race Face Turbine 35mm 6° x 60-80mm
GRIPS	Rocky Mountain Lock On XC
SADDLE	WTB Silverado Race
SEATPOST	RockShox Reverb Stealth 30.9mm x 355-420mm

*Price, specification and availability subject to change without notice.



INSTINCT 950 MSL

CRS546



TECHNOLOGY



IMPROVEMENTS

Shimano SLX Brakes for Reliable Performance.

SunRINGLÉ Helix TR27 Rims: Wider Profile and Tubeless Compatible.

X Fusion HiLo Strate Seatpost: Internally Routed Dropper Post.

GEOMETRY

FRAME SIZE		SM	MD	LG	XXL	XXL
HEAD ANGLE	degrees	67.7° - 69.3°	67.7° - 69.3°	67.7° - 69.3°	67.7° - 69.3°	67.7° - 69.3°
SEAT ANGLE	degrees	73.7° - 75.3°	73.7° - 75.3°	73.7° - 75.3°	73.7° - 75.3°	73.7° - 75.3°
SEAT TUBE (CENTER BB TO TOP)	(mm)	394	432	470	508	546
HORIZONTAL TOP TUBE LENGTH	(mm)	553	577	600	625	650
HEAD TUBE LENGTH	(mm)	100	110	120	130	145
CHAINSTAY LENGTH	(mm)	452	452	452	452	452
BOTTOM BRACKET DROP	(mm)	39.6 to 20.7	39.6 to 20.7	39.6 to 20.7	39.6 to 20.7	39.6 to 20.7
STANDOVER HEIGHT	(mm)	736	736	736	736	736
WHEELBASE	(mm)	1110	1134	1158	1183	1210
REACH	(mm)	378 - 395	400 - 417	420 - 437	442 - 459	464 - 480
STACK	(mm)	605 - 594	614 - 603	624 - 612	633 - 621	647 - 634

* More details on measurements on demand.

SPECIFICATIONS

FRAME	C13 Hi Mod Carbon Smoothwall Monocoque Front Triangle. FORM™ 7005 Series Custom Hydroformed Rear Triangle. ABC™ Pivots. Tapered Head Tube. Press Fit BB. Internal Cable Routing. ISCG05 Tabs. RIDE-9™ Adjustable Geometry + Suspension Rate
COLOR	Matte Dark Red
SIZES	S - M - L - XL - XXL
SHOCK	Fox Float CTD Custom Race Valved. SmoothLink™ Design 130mm. Rebound / Climb (Lockout) - Trail (ProPedal) - Descend (Open) Settings / Adjustable Suspension Rate
FORK	Fox 32 Float 29 130 CTD. 130mm. Rebound / Climb (Lockout) - Trail (Compression) - Descend (Open) Settings / 15mm Axle / Tapered Steerer
HEADSET	Cane Creek Fiften Series: IS42mm Top / IS52mm Bottom Tapered
BRAKE LEVERS	Shimano SLX
BRAKES	Shimano SLX Hydraulic Disc 180mm
CASSETTE	Shimano HG50 11-36T 10spd
CHAIN	Shimano HG54 10spd
CRANKS	Race Face Evolve 170-175mm Bash/36/22T 2x10spd
BOTTOM BRACKET	Race Face Press Fit Team XC
SHIFTERS	Sram X7 Triggers 2x10spd
F. DERAILLEUR	Sram X7 S3 Direct Mount 2x10spd
R. DERAILLEUR	Sram X9 Type 2 All Mountain 10spd
F. HUB	Shimano SLX / Centerlock / 32H / 15mm Axle
R. HUB	Shimano SLX / Centerlock / 32H / 12 x 142mm Axle
SPOKES	DT Swiss Competition
RIMS	Wheeltech Helix TR27 Tubeless Compatible by SUNringlé
TIRES	Maxxis F: Ardent EXO Folding 29" x 2.4" R: Ikon EXO Folding 29" x 2.35"
HANDELBAR	Race Face Evolve 1/2 Rise Ø31.8mm x 750mm x 9° Sweep
STEM	Race Face 6° x 60-80mm
GRIPS	Rocky Mountain Lock On XC
SADDLE	WTB Volt Race
SEATPOST	X Fusion HiLo Strate 30.9mm x 420mm

*Price, specification and availability subject to change without notice.



INSTINCT 950

CRS544

BC EDITION



TECHNOLOGY



GEOMETRY

FRAME SIZE		SM	MD	LG	XL	XXL
HEAD ANGLE	degrees	66.7° - 68.3°	66.7° - 68.3°	66.7° - 68.3°	66.7° - 68.3°	66.7° - 68.3°
SEAT ANGLE	degrees	72.8° - 74.3°	72.8° - 74.3°	72.8° - 74.3°	72.8° - 74.3°	72.8° - 74.3°
SEAT TUBE (CENTER BB TO TOP)	(mm)	394	432	470	508	546
HORIZONTAL TOP TUBE LENGTH	(mm)	553	577	600	625	650
HEAD TUBE LENGTH	(mm)	100	110	120	130	145
CHAINSTAY LENGTH	(mm)	452	452	452	452	452
BOTTOM BRACKET DROP	(mm)	31.9 to 12.4	31.9 to 12.4	31.9 to 12.4	31.9 to 12.4	31.9 to 12.4
STANDOVER HEIGHT	(mm)	745	745	745	745	745
WHEELBASE	(mm)	1119	1143	1167	1192	1219
REACH	(mm)	367 - 384	389 - 406	409 - 426	432 - 449	453 - 470
STACK	(mm)	611 - 600	621 - 610	631 - 620	641 - 629	655 - 643

* More details on measurements on demand.

SPECIFICATIONS

FRAME	FORM™ 7005 Series Custom Hydroformed Alloy. ABC™ Pivots. Tapered Head Tube. Press Fit BB. Internal Cable Routing. ISCG05 Tabs. RIDE-9™ Adjustable Geometry + Suspension Rate
COLOR	Matte Blue
SIZES	S - M - L - XL - XXL
SHOCK	X Fusion 02 RLX Custom Trail Valved. SmoothLink™ Design 130mm. Rebound / 3 Position Compression Settings / Adjustable Suspension Rate
FORK	X Fusion 140 Trace RL2. 34mm Stanchions / Lockout / Rebound / 15mm XLock / Tapered Steerer
HEADSET	Cane Creek Fifteen Series: Z544mm Top / Z556mm Bottom Tapered
BRAKE LEVERS	Shimano SLX
BRAKES	Shimano SLX Ice-Tec Hydraulic Disc 180mm
CASSETTE	Sram XG-1180 10-42T 11spd
CHAIN	KMC X11 11spd
CRANKS	Race Face Ride 170-175mm 30T 1x11spd
BOTTOM BRACKET	Race Face Press Fit Team XC
SHIFTERS	Sram X1 Trigger 1x11spd
F. DERAILLEUR	N/A
R. DERAILLEUR	Sram X1 Type 2 All Mountain 11spd
F. HUB	Sram MTH 716 / 6 Bolt / 15mm Axle
R. HUB	Sram MTH 746 / 6 Bolt / XD Freehub Body / 12 x 142mm Axle
SPOKES	DT Swiss Competition
RIMS	Wheeltech Inferno 27 by SUNringlé
TIRES	Maxxis DHRII EXO Folding 29" x 2.3"
HANDELBAR	Race Face Evolve 1/2 Rise Ø31.8mm x 750mm x 9° Sweep
STEM	Race Face 6° x 60-80mm
GRIPS	Rocky Mountain Lock On XC
SADDLE	WTB Volt Race
SEATPOST	X Fusion HiLo Ace 30.9mm x 420mm

*Price, specification and availability subject to change without notice.



INSTINCT 950

CRS543



TECHNOLOGY



IMPROVEMENTS

SunRINGLÉ Inferno 27 Rims: Wider Profile for Stiffer Wheel and Bigger Tire Contact Patch.

High Performance Maxxis Folding Tires.

GEOMETRY

FRAME SIZE		SM	MD	LG	XL	XXL
HEAD ANGLE	degrees	67.7° - 69.3°	67.7° - 69.3°	67.7° - 69.3°	67.7° - 69.3°	67.7° - 69.3°
SEAT ANGLE	degrees	73.7° - 75.3°	73.7° - 75.3°	73.7° - 75.3°	73.7° - 75.3°	73.7° - 75.3°
SEAT TUBE (CENTER BB TO TOP)	(mm)	394	432	470	508	546
HORIZONTAL TOP TUBE LENGTH	(mm)	553	577	600	625	650
HEAD TUBE LENGTH	(mm)	100	110	120	130	145
CHAINSTAY LENGTH	(mm)	452	452	452	452	452
BOTTOM BRACKET DROP	(mm)	39.6 to 20.7	39.6 to 20.7	39.6 to 20.7	39.6 to 20.7	39.6 to 20.7
STANDOVER HEIGHT	(mm)	736	736	736	736	736
WHEELBASE	(mm)	1110	1134	1158	1183	1210
REACH	(mm)	378 - 395	400 - 417	420 - 437	442 - 459	464 - 480
STACK	(mm)	605 - 594	614 - 603	624 - 612	633 - 621	647 - 634

* More details on measurements on demand.

SPECIFICATIONS

FRAME	FORM™ 7005 Series Custom Hydroformed Alloy. ABC™ Pivots. Tapered Head Tube. Press Fit BB. Internal Cable Routing. ISCG05 Tabs. RIDE-9™ Adjustable Geometry + Suspension Rate
COLOR	Matte Black
SIZES	S - M - L - XL - XXL
SHOCK	Fox Float CTD Custom Race Valved. SmoothLink™ Design 130mm. Rebound / Climb (Lockout) - Trail (ProPedal) - Descend (Open) Settings / Adjustable Suspension Rate
FORK	Fox 32 Float 29 130 CTD. 130mm. Rebound / Climb (Lockout) - Trail (Compression) - Descend (Open) Settings / 15mm Axle / Tapered Steerer
HEADSET	Cane Creek Fifteen Series: Z544mm Top / Z556mm Bottom Tapered
BRAKE LEVERS	Shimano SLX I-Spec Shifter Mount
BRAKES	Shimano SLX Hydraulic Disc 180mm
CASSETTE	Shimano HG50 11-36T 10spd
CHAIN	Shimano HG54 10spd
CRANKS	Race Face Evolve 170-175mm Bash/36/22T 2x10spd
BOTTOM BRACKET	Race Face Press Fit Team XC
SHIFTERS	Shimano SLX Rapid Fire I-Spec 2x10spd
F. DERAILLEUR	Sram X7 S3 Direct Mount 2x10spd
R. DERAILLEUR	Shimano XT Shadow Plus Direct Mount 10spd
F. HUB	Shimano SLX / Centerlock / 32H / 15mm Axle
R. HUB	Shimano SLX / Centerlock / 32H / 12 x 142mm Axle
SPOKES	DT Swiss Competition
RIMS	Wheeltech Inferno 27 by SUNringlé
TIRES	Maxxis F: Ardent EXO Folding 29" x 2.4" R: Ikon EXO Folding 29" x 2.35"
HANDELBAR	Race Face Evolve 1/2 Rise Ø31.8mm x 750mm x 9° Sweep
STEM	Race Face 6° x 60-80mm
GRIPS	Rocky Mountain Lock On XC
SADDLE	WTB Volt Race
SEATPOST	Rocky Mountain SL 30.9mm x 400mm

*Price, specification and availability subject to change without notice.



INSTINCT 930

CRS540



TECHNOLOGY



IMPROVEMENTS

Manitou Minute Expert Fork: Supple TPC Damping and Hydraulic Bottom Out Control.

SunRINGLÉ Inferno 27 Rims: Wider Profile for Stiffer Wheel and Bigger Tire Contact Patch.

High Performance Maxxis Folding Tires.

GEOMETRY

FRAME SIZE		SM	MD	LG	XL	XXL
HEAD ANGLE	degrees	67.7° - 69.3°	67.7° - 69.3°	67.7° - 69.3°	67.7° - 69.3°	67.7° - 69.3°
SEAT ANGLE	degrees	73.7° - 75.3°	73.7° - 75.3°	73.7° - 75.3°	73.7° - 75.3°	73.7° - 75.3°
SEAT TUBE (CENTER BB TO TOP)	(mm)	394	432	470	508	546
HORIZONTAL TOP TUBE LENGTH	(mm)	553	577	600	625	650
HEAD TUBE LENGTH	(mm)	100	110	120	130	145
CHAINSTAY LENGTH	(mm)	452	452	452	452	452
BOTTOM BRACKET DROP	(mm)	39.6 to 20.7	39.6 to 20.7	39.6 to 20.7	39.6 to 20.7	39.6 to 20.7
STANDOVER HEIGHT	(mm)	736	736	736	736	736
WHEELBASE	(mm)	1110	1134	1158	1183	1210
REACH	(mm)	378 - 395	400 - 417	420 - 437	442 - 459	464 - 480
STACK	(mm)	605 - 594	614 - 603	624 - 612	633 - 621	647 - 634

* More details on measurements on demand.

SPECIFICATIONS

FRAME	FORM™ 7005 Series Custom Hydroformed Alloy. ABC™ Pivots. Tapered Head Tube. Press Fit BB. Internal Cable Routing. ISCG05 Tabs. RIDE-9™ Adjustable Geometry + Suspension Rate
COLOR	Matte Blue
SIZES	S - M - L - XL - XXL
SHOCK	Fox Float CTD Custom Race Valved. SmoothLink™ Design 130mm. Rebound / Climb (Lockout) - Trail (ProPedal) - Descend (Open) Settings / Adjustable Suspension Rate
FORK	Manitou Minute Expert. 130mm. TPC Absolute+ Damper / Hydraulic Bottom Out / Compression / Lockout / Rebound / 15mm Hexlock Axle / Tapered Steerer
HEADSET	Cane Creek Fifteen Series: Z544mm Top / Z556mm Bottom Tapered
BRAKE LEVERS	Shimano M506 I-Spec Shifter Mount
BRAKES	Shimano M506 Hydraulic Disc 180mm
CASSETTE	Shimano HG50 11-36T 10spd
CHAIN	Shimano HG54 10spd
CRANKS	Race Face Ride 170-175mm Bash/36/22T 2x10spd
BOTTOM BRACKET	Race Face Press Fit Team XC
SHIFTERS	Shimano Deore Rapid Fire I-Spec 2x10spd
F. DERAILLEUR	Sram X5 S3 Direct Mount 2x10spd
R. DERAILLEUR	Shimano XT Shadow Plus Direct Mount 10spd
F. HUB	Shimano 618 / Centerlock / 32H / 15mm Axle
R. HUB	Shimano 618 / Centerlock / 32H / 12 x 142mm Axle
SPOKES	DT Swiss Champion
RIMS	Wheeltech Inferno 27 by SunRINGLÉ
TIRES	Maxxis F: Ardent EXO Folding 29" x 2.4" R: Ikon EXO Folding 29" x 2.35"
HANDELBAR	Race Face Ride 1/2 Rise Ø31.8mm x 740mm x 9° Sweep
STEM	Race Face 6° x 60-80mm
GRIPS	Rocky Mountain Lock On XC
SADDLE	WTB Volt Race
SEATPOST	Rocky Mountain SL 30.9mm x 400mm

*Price, specification and availability subject to change without notice.