

JARIFA² EQUIPPED

DU BIST BEREIT FÜR DAS RUND-UM-SORGLOS-PAKET.

Eines Tages möchte ich mal ... Erfahre all das, wovon du bisher nur geträumt hast. Sieben Sachen in die Gepäcktaschen, einfach machen – das JARIFA² EQUIPPED bietet dir die Möglichkeit dazu. Dank der umfangreichen Ausstattung und vielen weiteren Optionen, Anbauteile zu montieren, ist für alle Eventualitäten gesorgt. Die SQUARED EXPERIENCE unterstützt deinen Entdeckerdrang. Das einzige, worum Du dich kümmern musst, ist deine nächste Reiseroute.

VORBEREITET

Egal ob deine Reise mehrere Tage dauert oder du einfach viel transportieren musst: Das JARIFA² EQUIPPED ist genauso bereit für Bikepacking-Trips wie für städtische Lastenfahrten.

TROCKEN & SAUBER

Dank eines passenden Schutzblechs bleiben deine Kleidung und du trocken und sauber.

INTEGRIERT

Unsere XXL-Batterie mit bis zu 612 Wh versteckt sich form-schön integriert im Unterrohr, lässt sich aber jederzeit herausnehmen.



Einsatzgebiet: Trekkingtouren und Pendeln SQUARED, mehr erleben durch Motorunterstützung | 100 mm Federweg | Hardtail | variables E-Bike für Stadt und Land



GABELVARIANTE	100 MM			
Raddurchmesser	29"	29"	29"	29"
Rahmengröße	S	M	L	XL
Sitzrohlänge (mm)	400	440	480	520
Oberrohrlänge (mm)	589	602	615	628
Lenkwinkel (°)	70	70	70	70
Sitzwinkel (°)	74	74	74	74
Kettenstrebenlänge (mm)	490	490	490	490
Tretlagerabsenkung (mm)	60	60	60	60
Steuerröhlänge (mm)	120	120	140	160
Gabelaufbauhöhe (mm)	509	509	509	509
Gabelvorbiegung (mm)	51	51	51	51
Radstand (mm)	1.145	1.155	1.177	1.194
Stack (mm)	627	636	655	674
Reach (mm)	395	405	420	430



JARIFA² PRO EQUIPPED



6061 aluminium, 148x12 mm through axle
 Bosch Performance CX, 75 Nm, 250 W
 SR Suntour Raidon RL, 110x15 mm QR, 100 mm travel
 Shimano Deore M6000, 200 mm / 180 mm



JARIFA² EQUIPPED



6061 aluminium, 148x12 mm through axle
 Bosch Performance CX, 75 Nm, 250 W
 SR Suntour Raidon RL, 110x15 mm QR, 100 mm travel
 Shimano Deore M6000, 200 mm / 180 mm




JARIFA² ACTIVE EQUIPPED



6061 aluminium, 148x12 mm through axle
 Bosch Active Plus, 50 Nm, 250 W
 SR Suntour XCR 34 Coil, 110x15 mm QR, 100 mm travel
 Shimano M315, 180 mm / 160 mm



JARIFA² ISTREET SPEED



6061 aluminium, 142x12 mm through axle
 Impulse Evo RS, 80 Nm, 350 W
 RST Pulse Air, LO, 100x15 mm QR, 75 mm travel
 Magura MT4 SPEED, 180 mm / 180 mm



JARIFA² ISTREET PRO



6061 aluminium, 142x12 mm through axle
 Impulse Evo RS, 80 Nm, 250 W
 RST Pulse Air, LO, 100x15 mm QR, 75 mm travel
 Shimano M315, 180 mm / 160 mm



JARIFA² ISTREET



6061 aluminium, 142x12 mm through axle
 Impulse Evo RS, 80 Nm, 250 W
 RST Pulse LO, 9 mm QR, 75 mm travel
 Shimano M315, 180 mm / 160 mm

JARIFA² PRO EQUIPPED



WHEEL SIZE	SIZE/CM	ARTICLE NO. EU/Col.1	EU/Col.2
27,5"	XS/36	628 518 060	628 518 090
27,5"	S/40	628 518 061	628 518 091
29"	S/40	628 518 062	628 518 092
29"	M/44	628 518 063	628 518 093
29"	L/48	628 518 064	628 518 094
29"	XL/52	628 518 065	628 518 095

- 6061 aluminium, 148x12 mm through axle, internal cable routing, post mount 180 mm
- SR Suntour Raidon RL, 110x15 mm QR, 100 mm travel
- Bosch Performance CX, 75 Nm, 250 W, 50-300% support power
- BOSCH Powertube, 500 Wh, removeable
- Bosch, 4 Amp
- BOSCH Intuvia
- Shimano Deore XT 8000, 11-speed
- Shimano SLX 7000
- Shimano SLX 11S, 11-46T
- FSA, 18T
- BBB, aluminium, flatbar, 720 mm, rise: 0 mm, backsweep: 9°
- BBB, aluminium, 65 mm
- Acros AZX-212 AH, 1-1/8", tapered, 44/286-ZS56/40
- Sport Saddle
- JD low dropper YSP 15, 31,6 mm, internal
- Shimano Deore M6000, 200 mm / 180 mm
- DT-Swiss H 1900, 27": 584-30, 29": 622-30, 148x12 mm / 110x15 mm
- Continental X King 2.4
- Buechel Aluminium
- Racktime, w/integrated rear light
- Supernova Mini 2, power LED, custom
- Busch & Müller integrated with Line-Tec-Technologie
- Rear kickstand
- [1] Sealblue matt, [2] Havannabrown matt

JARIFA² EQUIPPED



WHEEL SIZE	SIZE/CM	ARTICLE NO. EU/Col.1	EU/Col.2
27,5"	XS/36	628 518 070	628 518 120
27,5"	S/40	628 518 071	628 518 121
29"	S/40	628 518 072	628 518 122
29"	M/44	628 518 073	628 518 123
29"	L/48	628 518 074	628 518 124
29"	XL/52	628 518 075	628 518 125

- 6061 aluminium, 148x12 mm through axle, internal cable routing, post mount 180 mm
- SR Suntour Raidon RL, 110x15 mm QR, 100 mm travel
- Bosch Performance CX, 75 Nm, 250 W, 50-300% support power
- BOSCH Powertube, 500 Wh, removeable
- Bosch compact, 2 Amp
- BOSCH Purion with Control panel, walk assist
- Shimano Deore XT 786, 10-speed
- Shimano SLX 7000
- Sunrace 11S, 11-40T
- FSA, 18T
- BBB, aluminium, flatbar, 720 mm, rise: 0 mm, backsweep: 9°
- BBB, aluminium, 65 mm
- Acros AZX-212 AH, 1-1/8", tapered, 44/286-ZS56/40
- Sport Saddle
- JD low dropper YSP 15, 31,6 mm, internal
- Shimano Deore M6000, 200 mm / 180 mm
- Rodi Tryp 25, 27": 584-25, 29": 662-25, Shimano Deore, 148x12 mm / 110x15 mm
- Continental Double Fighter III 50-622
- Buechel Aluminium
- Racktime, w/integrated rear light
- Supernova Mini 2, power LED, custom
- Busch & Müller integrated with Line-Tec-Technologie
- Rear kickstand
- [1] Sealblue matt, [2] Havannabrown matt

JARIFA² ACTIVE EQUIPPED



WHEEL SIZE	SIZE/CM	ARTICLE NO.	
		EU/Col.1	EU/Col.2
27,5"	XS/36	628 518 080	628 518 130
27,5"	S/40	628 518 081	628 518 131
29"	S/40	628 518 082	628 518 132
29"	M/44	628 518 083	628 518 133
29"	L/48	628 518 084	628 518 134
29"	XL/52	628 518 085	628 518 135



[2] Havannabrown matt

[1] Sealblue matt

- ⚙️ 6061 aluminium, 148x12 mm through axle, internal cable routing, post mount 180 mm
- 🔧 SR Suntour XCR 34 Coil, 110x15 mm QR, 100 mm travel
- 🔊 Bosch Active Plus, 50 Nm, 250 W, 50-250% support power
- 🔋 BOSCH Powertube, 500 Wh, removeable
- 🔌 Bosch compact, 2 Amp
- 📱 BOSCH Purion with Control panel, walk assist
- 🚲 Shimano Deore 6000, 10-speed
- 🚲 Shimano Deore 6000
- 🚲 Shimano Deore 10S, 11-42T
- 🚲 FSA, 36T
- 🚲 BBB, aluminium, flatbar, 720 mm, rise: 0 mm, backsweep: 9°
- 🚲 BBB, aluminium, 65 mm
- 🚲 1-1/8", tapered, 44/286-ZS56/40
- 🚲 Sport Saddle
- 🚲 BBB-BSP-20, 31.6 mm, 350mm
- 🚲 Shimano M315, 180 mm / 160 mm
- 🚲 Rodi Tryp 25, 27": 584-25, 29": 662-25, Shimano Deore, 148x12 mm / 110x15 mm
- 🚲 Continental Double Fighter III 50-622
- 🚲 (1) Sealblue matt,
- 🚲 (2) Havannabrown matt

JARIFA² | STREET SPEED



WHEEL SIZE	SIZE/CM	ARTICLE NO.	
		EU	
28" Gent	S/42	628 511 910	
28" Gent	M/46	628 511 911	
28" Gent	L/50	628 511 912	
28" Gent	XL/54	628 511 913	

- ⚙️ 6061 aluminium, 142x12 mm through axle, RAT Evo technology, internal cable routing, post mount 160 mm
- 🔧 RST Pulse Air, LO, 100x15 mm QR, 75 mm travel
- 🔊 Impulse Evo RS, 80 Nm, 350 W
- 🔋 Impulse, 612 Wh, removeable
- 🔌 BMZ DCW-0X
- 📱 Dayton
- 🚲 Shimano Deore XT 786, 10-speed
- 🚲 Shimano Deore 6000
- 🚲 SUNRACE 10S, 11-40T
- 🚲 MIRANDA IMPULSE
- 🚲 BBB, aluminium, flatbar, 720 mm, rise: 0 mm, backsweep: 9°
- 🚲 BBB, aluminium, 90 mm
- 🚲 Acros AZX-212 AH, 1-1/8", tapered, 44/286-ZS56/40
- 🚲 Sport Saddle
- 🚲 JD low dropper YSP 15, 31,6 mm, internal
- 🚲 Magura MT4 SPEED 180 mm / 180 mm
- 🚲 DT-Swiss M 1900, CL, 622-23, 142x12 mm / 100x15 mm
- 🚲 Continental Top Contact II 47
- 🚲 Buechel Aluminium, 60 mm
- 🚲 Racktime Focus custom, tubular aluminium
- 🚲 Supernova E3 V6S, Power LED, 165 lm
- 🚲 Busch & Müller Topline Light speed
- 🚲 Platform, Aluminium body
- 🚲 Rear Kickstand, aluminium
- 🚲 Nimbusgrey matt

JARIFA² | STREET PRO



[Gent] Nimbusgrey matt

[Lady] Maliblue

WHEEL SIZE	SIZE/CM	ARTICLE NO. EU
28" Gent	S/42	628 511 100
28" Gent	M/46	628 511 101
28" Gent	L/50	628 511 102
28" Gent	XL/54	628 511 103
28" Lady	S/42	628 511 105
28" Lady	M/46	628 511 106

- 6061 aluminium, 142x12 mm through axle, RAT Evo technology, internal cable routing, post mount 160 mm
- RST Pulse Air, LO, 100x15 mm QR, 75 mm travel
- 80 mm
- Impulse Evo RS, 80 Nm, 250 W
- Impulse, 612 Wh, removeable
- BMZ DCW-0X
- Dayton
- Shimano Deore XT 786, 10-speed
- Shimano Deore 6000
- SUNRACE 10S, 11-40T
- MIRANDA IMPULSE
- BBB, aluminium, flatbar, 720 mm, rise: 0 mm, backsweep: 9°
- BBB, aluminium, 90 mm
- Acros AZX-212 AH, 1-1/8", tapered, 44/286-ZS56/40
- Sport Saddle
- JD low dropper YSP 15, 31,6 mm, internal
- Shimano M315, 180 mm / 160 mm
- Rodi Ready 27, 662-27, Shimano Deore, 148x12 mm / 110x15 mm
- Continental Contact II
- Buechel Aluminium, 60 mm
- Racktime Focus custom, tubular aluminium, w/integrated rear light
- Supernova E3 V6S, Power LED, 165 lm
- Busch & Müller integrated with LineTec-Technologie
- Platform, Aluminium body
- Rear Kickstand, aluminium
- Gent: Nimbusgrey matt, Lady: Maliblue

JARIFA² | STREET



[Gent] Nimbusgrey matt

[Lady] White

WHEEL SIZE	SIZE/CM	ARTICLE NO. EU
28" Gent	S/42	628 511 110
28" Gent	M/46	628 511 111
28" Gent	L/50	628 511 112
28" Gent	XL/54	628 511 113
28" Lady	S/42	628 511 115
28" Lady	M/46	628 511 116

- 6061 aluminium, 142x12 mm through axle, RAT Evo technology, internal cable routing, post mount 160 mm
- RST Pulse, LO, 9 mm QR, 75 mm travel
- 80 mm
- Impulse Evo RS, 80 Nm, 250 W
- Impulse, 612 Wh, removeable
- BMZ DCW-0X
- Dayton
- Shimano Deore 591, 9-speed
- Shimano Altus 2000
- Shimano HG200 11-36T
- MIRANDA IMPULSE
- BBB, aluminium, flatbar, 720 mm, rise: 0 mm, backsweep: 9°
- BBB, aluminium, 90 mm
- 1-1/8", tapered, 44/286-ZS56/40
- Sport Saddle
- BBB-BSP-20, 31,6 mm, 350mm
- Shimano M315, 180 mm / 160 mm
- Rodi Tryp 584/662-25, Shimano Deore, 148x12 mm / 110x15 mm
- Continental Contact II
- Buechel Aluminium, 60 mm
- Racktime Focus custom, tubular aluminium, w/integrated rear light
- Supernova E3 V6S, Power LED, 165 lm
- Busch & Müller integrated with LineTec-Technologie
- Platform, Aluminium body
- Rear Kickstand, aluminium
- Gent: Nimbusgrey matt, Lady: White